GLASS FABRIC CLAMP LINER +450 °C
EME-WCL2-UC

Prevents corrosion problems
Glass fabric clamp liner eliminates corrosion problems due to electrolytic action between dissimilar metals of pipe and pipe clamp.

Ease of installation
Flexible liner easy to install around the pipe.

Fields of application
- Preventign corrosion between pipe and clamp
- Protecting coating of pipe
- Isolation

Material
Glass fabrics made from texturized yarn

Finish: uncoated

Optional: coatings for specific applications or to prevent unraveling or to suit speciifc higher or cryogenic temperatures.

Temperature range: -30^0 C up to 450^0 C
(depending on application)

Resistant to most common oils and chemicals; please ask for details

Standard size : roll length 50 m
Pre-cut woven width: 50, 60, 75, 100, 110 and 150 mm
Nominal thickness: ca. 3 mm
Compressed thickness: ca. 2 mm
Other sizes or thicknesses upon request

Minimum standard take-off quantity: 50 m

Product codes:

EME-WCL2-UC-040	old code EME-WCL2-040
EME-WCL2-UC-050	old code EME-WCL2-050
EME-WCL2-UC-060	old code EME-WCL2-060
EME-WCL2-UC-075	old code EME-WCL2-075
EME-WCL2-UC-100	old code EME-WCL2-100
EME-WCL2-UC-110	old code EME-WCL2-110
EME-WCL2-UC-150	old code EME-WCL2-150

Issue 2024

Esmat manufactured products sold by sister trading company Synthesis bv
Gildenweg 5
8304 BD Emmeloord
The Netherlands

Phone: +31 (0)321 33 88 45
+31 (0)321 380 457
info@synthesisbv.nl